

Electronics module for ET 200S, 8 DO Sink Output, 24 V DC/0.5 A, 15 mm width, 1 unit per packing unit



Supply voltage

Reverse voltage protection	Yes; when using the same correctly polarized load voltage as on the power module
----------------------------	--

Load voltage L+

- | | |
|---|---|
| <ul style="list-style-type: none"> • Rated value (DC) • Reverse polarity protection | <p>24 V; From power module</p> <p>Yes</p> |
|---|---|

Input current

from load voltage L+ (without load), max.	5 mA
from backplane bus 3.3 V DC, max.	10 mA

Power loss

Power loss, typ.	1.5 W
------------------	-------

Address area

Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	1 byte

Digital outputs

Number of digital outputs	8
Short-circuit protection	Yes

• Response threshold, typ.	1.5 A
Limitation of inductive shutdown voltage to	Typ. 47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	3 400 Ω
Output voltage	
• for signal "1", min.	Max. 1 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	5 μA
Output delay with resistive load	
• "0" to "1", max.	300 μs
• "1" to "0", max.	600 μs
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; per module
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per module, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
• Status indicator digital output (green)	Yes
Parameter	
Remark	3 byte
Potential separation	
Potential separation digital outputs	

- between the channels
- between the channels and backplane bus

No
Yes

Isolation

Isolation tested with 500 V DC

Dimensions

Width 15 mm

Height 81 mm

Depth 52 mm

Weights

Weight, approx. 40 g

last modified: 05/09/2019