

SIMATIC DP, Electronics module 2 AI U High Feature f. ET200S, 15 mm width, Cycle time per module: 0.5 ms, +/-10V; 15 bit+sign, +/-5 V; 15 bit+sign, 1.5 V; 15 bit, Operational limit +/-0.1% with SF LED (group fault)



### Supply voltage

#### Load voltage L+

- Rated value (DC) 24 V
- Reverse polarity protection Yes

### Input current

from load voltage L+ (without load), max.	55 mA
from backplane bus 3.3 V DC, max.	10 mA

### Output voltage

#### Power supply to the transmitters

- present No

### Power loss

Power loss, typ.	0.85 W
------------------	--------

### Address area

#### Address space per module

- Address space per module, max. 4 byte

### Analog inputs

Number of analog inputs	2
-------------------------	---

permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous; 75 V for max. 1 ms
Cycle time (all channels) max.	0.5 ms; 0.5 ms for 2 channels without noise suppression, 18 / 21 ms per channel with noise suppression
<b>Input ranges (rated values), voltages</b>	
• 1 V to 5 V	Yes
• Input resistance (1 V to 5 V)	800 kΩ
• -10 V to +10 V	Yes
• Input resistance (-10 V to +10 V)	800 kΩ
• -5 V to +5 V	Yes
• Input resistance (-5 V to +5 V)	800 kΩ
<b>Cable length</b>	
• shielded, max.	200 m
<b>Analog value generation for the inputs</b>	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; 0 to 5 V: 15 bit, ±10 V: 16 bit, ±5 V: 16 bit
• Integration time, parameterizable	Yes
• Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz / no
• Conversion time (per channel)	0.04 ms; Without noise suppression 17/20 ms per channel with error
<b>Smoothing of measured values</b>	
• parameterizable	Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time
• Step: None	Yes; 1x
• Step: low	Yes; 4x
• Step: Medium	Yes; 16x
• Step: High	Yes; 32x
<b>Encoder</b>	
Connection of signal encoders	
• for voltage measurement	Yes
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.003 %/K
Crosstalk between the inputs, min.	-100 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.01 %
<b>Operational error limit in overall temperature range</b>	
• Voltage, relative to input range, (+/-)	0.1 %; 0.2% without interference frequency suppression
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to input range, (+/-)	0.05 %; 0.1% without interference frequency suppression
Interference voltage suppression for $f = n \times (f_1 +/ - 1\%)$ , $f_1$ = interference frequency	

• Series mode interference (peak value of interference < rated value of input range), min.	90 dB
• Common mode interference (USS < 2.5 V) , min.	100 dB
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	Yes
<b>Interrupts/diagnostics/status information</b>	
Alarms	
• Hardware interrupt	Yes
Diagnostic messages	
• Wire-break	Yes; Measuring range 1 to 5 V only
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
<b>Parameter</b>	
Remark	12 bytes, 4 bytes in compatibility mode
Measurement type/range	deactivated / ±5 V / 1 to 5 V / ±10 V
Group diagnostics	Disable / enable
Overflow/underflow	Disable / enable
<b>Potential separation</b>	
Potential separation analog inputs	
• between the channels	No; however, increased permissible potential difference between the inputs.
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
<b>Permissible potential difference</b>	
between the inputs (UCM)	140 V DC/100 V AC
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Dimensions</b>	
Width	15 mm
Height	81 mm
Depth	52 mm
<b>Weights</b>	
Weight, approx.	45 g
last modified:	05/09/2019