

SIMATIC S7-200, CPU 221 Compact unit, AC power supply 6 DI
DC/4 DO Relay outputs, 4 KB progr./2 KB data



Figure similar

Supply voltage	
Rated value (AC)	
• 120 V AC	Yes
• 230 V AC	Yes
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	5 V
• permissible range, upper limit (DC)	30 V
Load voltage L1	
• Rated value (AC)	100 V; 100 V AC to 230 V AC
• permissible range, lower limit (AC)	5 V
• permissible range, upper limit (AC)	250 V
• permissible frequency range, lower limit	47 Hz
• permissible frequency range, upper limit	63 Hz
Input current	
Inrush current, max.	20 A; at 264 V

from supply voltage L1, max.	120 mA; 15 to 60 mA (240 V); 30 to 120 mA (120 V); output current for expansion modules (5 V DC) 340 mA
------------------------------	---

Encoder supply

24 V encoder supply	
• 24 V	Yes; Permissible range: 20.4V to 28.8V
• Short-circuit protection	Yes; electronic at 600 mA
• Output current, max.	180 mA

Power loss

Power loss, typ.	6 W
------------------	-----

Memory

Number of memory modules (optional)	1; pluggable memory module, content identical with integral EEPROM; can additionally store recipes, data logs and other files
-------------------------------------	---

Work memory	
• integrated (for program)	4 kbyte
• integrated (for data)	2 kbyte

Backup	
• present	Yes; Program: Entire program maintenance-free on integral EEPROM, programmable via CPU; data: Entire DB 1 loaded from PG/PC maintenance-free on integral EEPROM, current values of DB 1 in RAM, retentive memory bits, timers, counters, etc. maintenance-free via high-performance capacitor; optional battery for long-term buffering

Battery

Backup battery	
• Backup time, max.	50 h; (min. 8 h at 40 °C); 200 days (typ.) with optional battery module

CPU processing times

for bit operations, max.	0.22 µs
--------------------------	---------

Counters, timers and their retentivity

S7 counter	
• Number	256
Retentivity	
— adjustable	Yes; via high-performance capacitor or battery
— lower limit	1
— upper limit	256
Counting range	
— lower limit	0
— upper limit	32 767
S7 times	
• Number	256
Retentivity	

— adjustable	Yes; via high-performance capacitor or battery
— upper limit	64
Time range	
— lower limit	1 ms
— upper limit	54 min; 4 timers: 1 ms to 30 s; 16 timers: 10 ms to 5 min; 236 timers: 100 ms to 54 min

Data areas and their retentivity

Flag	
• Number, max.	32 byte
• Retentivity available	Yes; M 0.0 to M 31.7
• of which retentive with battery	0 to 255, via high-performance capacitor or battery, adjustable
• of which retentive without battery	0 to 112 in EEPROM, adjustable

Hardware configuration

connectable programming devices/PCs	SIMATIC PG/PC, standard PC
-------------------------------------	----------------------------

Digital inputs

Number of digital inputs	6; Integrated
Source/sink input	Yes; optionally, per group

Input voltage	
• Rated value (DC)	24 V
• for signal "0"	0 to 5 V
• for signal "1"	min. 15 V

Input current	
• for signal "1", typ.	2.5 mA

Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; all
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms

for interrupt inputs	
— parameterizable	Yes; I 0.0 to I 0.3

for technological functions	
— parameterizable	Yes; (E 0.0 to E 0.5) 30 kHz

Cable length	
• shielded, max.	500 m; Standard input: 500 m, high-speed counters: 50 m
• unshielded, max.	300 m; not for high-speed signals

Digital outputs

Number of digital outputs	4; Relays
Short-circuit protection	No; to be provided externally
Switching capacity of the outputs	
• with resistive load, max.	2 A

• on lamp load, max.	30 W with DC, 200 W with AC
Output voltage	
• for signal "1", min.	L+/L1
Output current	
• for signal "1" rated value	2 A
• for signal "0" residual current, max.	0 mA
Output delay with resistive load	
• "0" to "1", max.	10 ms; all outputs
• "1" to "0", max.	10 ms; all outputs
Parallel switching of two outputs	
• for uprating	No
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	6 A
horizontal installation	
— up to 55 °C, max.	6 A
Relay outputs	
• Number of relay outputs	4
• Number of relay outputs, integrated	4
• Number of operating cycles, max.	10 000 000; mechanically 10 million, at rated load voltage 100 000
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m

Analog inputs

Number of analog potentiometers	1; Analog potentiometer; resolution 8 bit
---------------------------------	---

Encoder

Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA

1. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Protocols	
• MPI	Yes; As MPI slave for data exchange with MPI masters (S7-300/S7-400 CPUs, OPs, TDs, Push Button Panels); S7-200-internal CPU/CPU communication is possible in the MPI network with restrictions; transmission rates: 19.2/187.5 kbit/s
• PPI	Yes; with PPI protocol for program functions, HMI functions (TD 200, OP), S7-200-internal CPU/CPU communication ; transmission rates 9.6/19.2/187.5 kbit/s

- serial data exchange

Yes; As freely programmable interface with interrupt facility for serial data exchange with third-party devices with ASCII protocol transfer rates: 1.2 / 2.4 / 4.8 / 9.6 / 19.2 / 38.4 / 57.6 / 115.2 kbps; the PC/PPI cable can also be used as RS 232/RS 485 converter

MPI

- Transmission rate, min. 19.2 kbit/s
- Transmission rate, max. 187.5 kbit/s

Integrated Functions

Number of counters	4; High-speed counters (30 kHz each), 32 bit (incl. sign), can be used as up/down counters or for connecting 2 incremental encoders with 2 pulse trains offset by 90° (max. 20 kHz (A/B counters)); parameterizable enable and reset input; interrupt facilities (incl. call of subroutine with any content) when the setpoint is reached; reversal in counting direction, etc.
Counting frequency (counter) max.	30 kHz
Number of alarm inputs	4; 4 rising edges and/or 4 falling edges

Potential separation

Potential separation digital inputs

- between the channels Yes
- between the channels, in groups of 2 and 4

Potential separation digital outputs

- between the channels Yes; Relays
- between the channels, in groups of 1 and 3

Permissible potential difference

between different circuits	500 V DC between 24 V DC and 5 V DC; 1500 V AC between 24 V DC and 230 V AC
----------------------------	---

Degree and class of protection

Degree of protection acc. to EN 60529

- IP20 Yes

Ambient conditions

Ambient temperature during operation

- horizontal installation, min. 0 °C
- horizontal installation, max. 55 °C
- vertical installation, min. 0 °C
- vertical installation, max. 45 °C

Air pressure acc. to IEC 60068-2-13

- permissible range, lower limit 860 hPa
- permissible range, upper limit 1 080 hPa

Relative humidity

- Operation, min. 5 %
- Operation, max. 95 %; RH class 2 in accordance with IEC 1131-2

Configuration

Programming

- | | |
|-------------------------------|---|
| • Command set | Bit logic instructions, compare instructions, timer instructions, counter instructions, clock instructions, transmissions instructions, table instructions, logic instructions, shift and rotate instructions, conversion instructions, program control instructions, interrupt and communications instructions, logic stack instructions, integer maths, floating-point math instructions, numerical functions |
| • Program processing | free cycle (OB 1), interrupt-controller, time-controlled (1 to 255 ms) |
| • Program organization | 1 OB, 1 DB, 1 SDB subroutines with/without parameter transfer |
| • Number of subroutines, max. | 64 |

Programming language

- | | |
|-------|-----|
| — LAD | Yes |
| — FBD | Yes |
| — STL | Yes |

Know-how protection

- | | |
|---|----------------------------------|
| • User program protection/password protection | Yes; 3-stage password protection |
|---|----------------------------------|

Connection method

- | | |
|-----------------------|----|
| Plug-in I/O terminals | No |
|-----------------------|----|

Dimensions

- | | |
|--------|-------|
| Width | 90 mm |
| Height | 80 mm |
| Depth | 62 mm |

Weights

- | | |
|-----------------|-------|
| Weight, approx. | 310 g |
|-----------------|-------|

last modified: 06/08/2019