

SIMATIC S7-400, analog input SM 431, isolated 16 AI; resolution 16 bit, U/I/Resistor/Thermocouple/Pt100 , alarm, diagnostics



Figure similar

| Supply voltage | |
|---|---|
| Load voltage L+ | |
| <ul style="list-style-type: none"> Rated value (DC) | 24 V; Only required for supplying 2-wire transmitters |
| <ul style="list-style-type: none"> Reverse polarity protection | Yes |
| Input current | |
| from load voltage L+ (without load), max. | 400 mA; for 16 connected, fully controlled 2-wire transmitters |
| from backplane bus 5 V DC, max. | 700 mA |
| Power loss | |
| Power loss, typ. | 4.5 W |
| Analog inputs | |
| Number of analog inputs | 16 |
| <ul style="list-style-type: none"> For voltage/current measurement | 16 |
| <ul style="list-style-type: none"> For resistance measurement | 8 |
| permissible input voltage for voltage input (destruction limit), max. | 18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20) |

| | |
|---|--------------|
| permissible input current for current input (destruction limit), max. | 40 mA |
| Input ranges | |
| • Voltage | Yes |
| • Current | Yes |
| • Thermocouple | Yes |
| • Resistance thermometer | Yes |
| • Resistance | Yes |
| Input ranges (rated values), voltages | |
| • 1 V to 5 V | Yes |
| • Input resistance (1 V to 5 V) | 1 M Ω |
| • -1 V to +1 V | Yes |
| • Input resistance (-1 V to +1 V) | 1 M Ω |
| • -10 V to +10 V | Yes |
| • Input resistance (-10 V to +10 V) | 1 M Ω |
| • -2.5 V to +2.5 V | Yes |
| • Input resistance (-2.5 V to +2.5 V) | 1 M Ω |
| • -25 mV to +25 mV | Yes |
| • Input resistance (-25 mV to +25 mV) | 1 M Ω |
| • -250 mV to +250 mV | Yes |
| • Input resistance (-250 mV to +250 mV) | 1 M Ω |
| • -5 V to +5 V | Yes |
| • Input resistance (-5 V to +5 V) | 1 M Ω |
| • -50 mV to +50 mV | Yes |
| • Input resistance (-50 mV to +50 mV) | 1 M Ω |
| • -500 mV to +500 mV | Yes |
| • Input resistance (-500 mV to +500 mV) | 1 M Ω |
| • -80 mV to +80 mV | Yes |
| • Input resistance (-80 mV to +80 mV) | 1 M Ω |
| Input ranges (rated values), currents | |
| • 0 to 20 mA | Yes |
| • Input resistance (0 to 20 mA) | 50 Ω |
| • -10 mA to +10 mA | Yes |
| • Input resistance (-10 mA to +10 mA) | 50 Ω |
| • -20 mA to +20 mA | Yes |
| • Input resistance (-20 mA to +20 mA) | 50 Ω |
| • 4 mA to 20 mA | Yes |
| • Input resistance (4 mA to 20 mA) | 50 Ω |
| • -5 mA to +5 mA | Yes |
| • Input resistance (-5 mA to +5 mA) | 50 Ω |
| Input ranges (rated values), thermocouples | |

- Type B
- Input resistance (Type B)
- Type E
- Input resistance (Type E)
- Type J
- Input resistance (type J)
- Type K
- Input resistance (Type K)
- Type L
- Input resistance (Type L)
- Type N
- Input resistance (Type N)
- Type R
- Input resistance (Type R)
- Type S
- Input resistance (Type S)
- Type T
- Input resistance (Type T)
- Type U
- Input resistance (Type U)

Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ

Input ranges (rated values), resistance thermometer

- Ni 100
- Input resistance (Ni 100)
- Ni 1000
- Input resistance (Ni 1000)
- Pt 100
- Input resistance (Pt 100)
- Pt 1000
- Input resistance (Pt 1000)
- Pt 200
- Input resistance (Pt 200)
- Pt 500
- Input resistance (Pt 500)

Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ

Input ranges (rated values), resistors

- 0 to 48 ohms
- Input resistance (0 to 48 ohms)
- 0 to 150 ohms
- Input resistance (0 to 150 ohms)
- 0 to 300 ohms
- Input resistance (0 to 300 ohms)
- 0 to 600 ohms

Yes
1 MΩ
Yes
1 MΩ
Yes
1 MΩ
Yes

| | |
|---|---|
| • Input resistance (0 to 600 ohms) | 1 MΩ |
| • 0 to 6000 ohms | Yes; Usable up to 5000 Ohm |
| • Input resistance (0 to 6000 ohms) | 1 MΩ |
| Thermocouple (TC) | |
| Temperature compensation | |
| — parameterizable | Yes |
| — external temperature compensation with Pt100 | Yes |
| — external temperature compensation with compensations socket | Yes |
| — dynamic reference temperature value | Yes |
| Characteristic linearization | |
| • parameterizable | Yes |
| — for thermocouples | Type B, E, J, K, L, N, R, S, T, U |
| — for resistance thermometer | Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000 |
| Cable length | |
| • shielded, max. | 200 m; 50 m with thermocouples and input ranges ≤ 80 mV |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| • Resolution with overrange (bit including sign), max. | 16 bit; 16 / 16 / 16 |
| • Integration time, parameterizable | Yes |
| • Basic conversion time (ms) | 6 / 20,1 / 23,5 ms |
| • Integration time (ms) | 2,5 / 16,7 / 20 ms |
| • Basic conversion time, including integration time (ms) | |
| — additional conversion time for wire-break monitoring | 4.3 / 4.3 / 4.3 ms |
| — additional conversion time for resistance measurement | 12 / 40,2 / 47 ms |
| — additional conversion time for wire-break monitoring and resistance measurement | 5,5 ms |
| • Interference voltage suppression for interference frequency f1 in Hz | 400 / 60 / 50 Hz |
| Encoder | |
| Connection of signal encoders | |
| • for voltage measurement | Yes; possible |
| • for current measurement as 2-wire transducer | Yes |
| • for current measurement as 4-wire transducer | Yes |
| • for resistance measurement with two-wire connection | Yes; Line resistances are also measured |

- for resistance measurement with three-wire connection
- for resistance measurement with four-wire connection

Yes

Yes

Errors/accuracies

Operational error limit in overall temperature range

- Voltage, relative to input range, (+/-) 0.3 %; ± 0.3 % at ± 250 mV, ± 500 mV, ± 1 V, ± 2.5 V, ± 5 V, 1 to 5 V, ± 10 V; ± 0.31 % at ± 80 mV; ± 0.32 % at ± 50 mV; ± 0.35 % at ± 25 mV
- Current, relative to input range, (+/-) 0.3 %; at 0 to 20 mA, ± 5 mA, ± 10 mA, ± 20 mA, 4 to 20 mA
- Resistance, relative to input range, (+/-) 0.3 %; ± 0.3 % at 0 to 48 Ohm (4-conductor measurement), 0 to 150 Ohm (4-conductor measurement), 0 to 300 Ohm (4-conductor measurement), 0 to 5000 Ohm (4-conductor measurement, in range of 6000 Ohm); ± 0.4 % at 0 to 300 Ohm (3-conductor measurement), 0 to 600 Ohm (3-conductor measurement), 0 to 5000 Ohm (3-conductor measurement, in range of 6000 Ohm);
- Resistance thermometer, relative to input range, (+/-) 0.4 %

Basic error limit (operational limit at 25 °C)

- Voltage, relative to input range, (+/-) 0.15 %; ± 0.15 % at ± 250 mV, ± 500 mV, ± 1 V, ± 2.5 V, ± 5 V, 1 V to 5 V, ± 10 V; ± 0.17 % at ± 80 mV; ± 0.19 % at ± 50 mV; ± 0.23 % at ± 25 mV
- Current, relative to input range, (+/-) 0.15 %; at 0 to 20 mA, ± 5 mA, ± 10 mA, ± 20 mA, 4 to 20 mA
- Resistance, relative to input range, (+/-) 0.15 %; ± 0.15 % at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement, in range of 6000 ohms); ± 0.3 % at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms)
- Resistance thermometer, relative to input range, (+/-) 0.3 %

Interrupts/diagnostics/status information

Alarms

- Diagnostic alarm Yes; Parameterizable
- Limit value alarm Yes; Parameterizable

Diagnostics indication LED

- internal fault INTF (red) Yes
- external fault EXTf (red) Yes

Potential separation

Potential separation analog inputs

- Potential separation analog inputs Yes; internal/external
- between the channels No

Isolation

| | |
|-----------------------|---|
| Isolation tested with | 2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground |
|-----------------------|---|

Dimensions

| | |
|--------|--------|
| Width | 25 mm |
| Height | 290 mm |
| Depth | 210 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 500 g |
|-----------------|-------|

last modified: 06/27/2019