

### Product type designation

Product description

### PB M12 connector

M12 connector with pin insert, 5-pole, B-coded

M12 connection plug for ET 200 with axial cable outlet for assembly in the field, Male contact insert, 1 pack=5 units



Figure similar

Suitability for use	For connecting electrical PB bus cables to ET200
<b>Transmission rate</b>	
Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
<b>Interfaces</b>	
Number of electrical connections	
• for PROFIBUS cables	1
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Integrated screw-type contacts for 2-core PB installation cables
• for network components or terminal equipment	M12 connector (male insert, 4-pin, B-coded)
Type of electrical connection / FastConnect	No
<b>Mechanical data</b>	
Material / of the enclosure	metal
Locking mechanism design	Screw

Design, dimensions and weight	
Type of cable outlet	180° cable outlet
Width	19 mm
Height	19 mm
Depth	73 mm
Net weight	40 g

Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +80 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +80 °C
Chemical resistance / to water	resistant
Protection class IP	IP65/67

Product properties, functions, components / general	
Product feature	
<ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes
Product component	
<ul style="list-style-type: none"> <li>strain relief</li> </ul>	Yes

Standards, specifications, approvals	
Certificate of suitability	
<ul style="list-style-type: none"> <li>RoHS conformity</li> </ul>	Yes
<ul style="list-style-type: none"> <li>UL approval</li> </ul>	No
<ul style="list-style-type: none"> <li>Railway application in accordance with EN 50155</li> </ul>	No

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> <li>to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>to website: CAx Download Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	05/15/2019