



## E32-T14L 2M

Fiber optic sensor head, through-beam, cylindrical radial, diameter 3 mm, R25 fiber, 2 m cable

# Specifications

|                                    |                    |
|------------------------------------|--------------------|
| <b>Sensing method</b>              | Through-beam       |
| <b>Shape</b>                       | Cylindrical radial |
| <b>Size</b>                        | dia 3 mm           |
| <b>Application</b>                 | Object detection   |
| <b>Features</b>                    | Miniature          |
| <b>Temperature range</b>           | -40-70 °C          |
| <b>Sensing distance</b>            | 1420 mm            |
| <b>Cable length</b>                | 2 m                |
| <b>Bending radius</b>              | 25 mm              |
| <b>Free cut</b>                    | ✓                  |
| <b>Material core</b>               | Plastic            |
| <b>Degree of protection (IP)</b>   | IP67               |
| <b>Sensing surface orientation</b> | Side-view          |
| <b>Material sheath</b>             | Polyethylene       |

# Related products



## E3NX-CA

High-performance color mark sensor



## E3NX-CA

High-performance color mark sensor



## E3NX-FA

High-performance digital fiber amplifier



## E3NX-MA

Smart Fiber Amplifier Units



## E3X-HD

Easy-teach digital fiber amplifier



## E3X-NA

Digital fiber amplifier with potentiometer adjustment



## E3X-SD

Single display digital fiber amplifier



## E3X-ZV and E3X-MZV

Smart Fiber Amplifier

# Downloads

CAD Library



## Fiber Optic Sensors Group Catalogue

EN PDF 7.54 MB

