


# Solenoid valve VUVG

Part number: 564212

FESTO



## Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Valve function	2x3/2-way, monostable, closed 2x3/2-way, open, monostable 2x3/2-way, open/closed, monostable 5/2 double solenoid 5/2-way, monostable 5/3-way, pressurised 5/3 exhausted 5/3 closed
Type of actuation	Electric
Valve size	14 mm
Standard nominal flow rate	90 l/min ... 1380 l/min
pneumatic working port	Flange M3 M5 M7 G1/8 G1/4 QS-3 QS-4 QS-6 QS-8 QS-10 QS-5/32 QS-1/8 QS-3/16 QS-1/4 QS-5/16 QS-3/8
Operating voltage	12V DC 24V DC 5V DC
Operating pressure	-0.09 MPa ... 1 MPa
Operating pressure	-0.9 bar ... 10 bar
Design	Piston gate valve
Type of reset	Mechanical spring Pneumatic spring
Approval	RCM trademark c UL us - Recognized (OL)
CE mark (see declaration of conformity)	To EU EMC Directive To EU Low Voltage Directive In accordance with EU RoHS Directive

Feature	Value
Degree of protection	IP40 IP65 With plug socket
Exhaust-air function	With flow control option
Sealing principle	Soft
Mounting position	optional
Manual override	Detenting Non-detenting Covered
Type of piloting	Pilot actuated
Pilot air supply	External Internal
lap	Positive overlap Indefinite overlap
Duty cycle	100%
Permissible voltage fluctuations	+/- 10 %
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Restrictions for environmental and media temperature	-5 ... 50° C Without holding current reduction
Corrosion resistance class CRC	2 - Moderate corrosion stress
Media temperature	-5 °C ... 60 °C
Ambient temperature	-5 °C ... 60 °C
Electrical connection	Via electrical sub-base
Type of mounting	Either: On manifold rail With through-hole
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Material seals	HNBR NBR
Material housing	Wrought aluminium alloy